

## 5000S / 5001S

### Control and indicating equipment



#### Features

- › 4 COM loops
- › 1020 addresses, 512 alarm points
- › Auto-addressing
- › Up to 30 control units in an EBL ring network
- › Redundant network with multi master configuration
- › Remote monitoring and operation available
- › Easy integration with building- and service management systems
- › Easy and flexible commissioning and service

#### General

- › Tested and approved according to EN54-2, EN54-4 and EN54-13
- › CPR: 0402-CPR-C500143, 0402-CPR-C500142

#### Order number

- › 5000SXX - EBL512 G3 Control Unit
- › 5000SPRTXX - EBL512 G3 Control Unit with printer
- › 5001S - EBL512 G3 Control Unit w.o. front

#### Related products

- › EBLWin for planning & commissioning
- › 5013 - Cabinet for drawings
- › 5014 - Cabinet for batteries up to 65Ah
- › 5020 - Mounting plate for 19" rack
- › 5068 - Frame for build-in installation
- › 4580 - 8 zones expansion board
- › 4581 - 8 relay outputs expansion board
- › 4583 - Inputs and outputs expansion board
- › 5088 - Gateway
- › 5040 - Network board



5000: 23,1 kg  
5001: 19 kg



5000: 628 x 438 x 187 mm  
5001: 625 x 418 x 177 mm



Built-in:  
max 2 x 28Ah



IP30



-5 TO +40 °C



230 V AC



<95%

